

2005-2012 FORD SUPERDUTY STEERING KNUCKLE

Reid Racing's high-steer Ford SuperDuty (2005-2012 F250, F350) steering knuckle is designed as a heavy-duty stock-replacement passenger-side knuckle that provides additional options for installing aftermarket steering linkage. The primary improvements over the OEM knuckle include a flat-top pad for a bolt-on steering arm, dual steering stops, and increased overall strength. The flat-top pad measures 4.5 inches higher than the cast-in steering arm's top surface, and aftermarket steering arms of various heights can accommodate a wide range of suspension lifts. All OEM parts including the unit-bearing, vacuum-operated lockout hub, stub shaft, and brakes are reused.

The cast-in steering arm is tapered from the top and bottom just as with the OEM knuckle, so the original steering linkage may be re-installed. If using an aftermarket high-steer arm with a new drag link, an OEM drag link end may be used to secure the tie rod end to the knuckle after cutting off the unused threaded portion of the drag link end. Aftermarket steering manufacturers have their own steering solutions available for the Reid Racing knuckle.

Although the Reid Racing knuckle will work on the similar later model year axles, Ford changed the brake calipers and knuckles for 2012.5 and later trucks. To use this knuckle on 2012.5+ axles, you must utilize an OEM 2005-2012 driver's side knuckle and brakes. Also note that the 10-lug "Super 60" axle found on some F450 & F550 trucks uses unique outer assemblies on which the OEM and Reid Racing F250 & F350 knuckles will not fit.

INSTALLATION

- Follow the basic steps in a factory instruction manual for disassembly and reassembly of the front axle. Clean and inspect all the original parts, replacing any damaged or worn components.
- Check clearance between the tie rod damper and the differential cover and adjust the bracket if necessary.
- Carefully route the ABS/Traction Control speed sensor wire between the brake backing plate and the high-steer arm to ensure it does not get pinched or abraded. Re-use the original clamp bolt from the original knuckle to secure the wire's molded rubber mount to the new location on the new knuckle.
- Install the rubber vacuum line to the port in its new location at the front of the steering knuckle and check that it does not stretch or pinch as the steering cycles full-left and full-right.
- Check the length of the steering stops; grind them shorter if necessary.
- A raised track bar bracket is recommended to minimize bump steer when utilizing a high-steer arm. Consult your high-steer arm manufacturer for recommendations.
- Five high-steer stud holes are tapped with 1/2"-20 fine threads for ARP Dana 60 studs (kit part # **D60117K**).
- Torque all fasteners according to the original specifications as per a factory service manual. Retorque after 200 miles and/or the first off-road trip.

WARNING

THE REID RACING, INC. SUPERDUTY STEERING KNUCKLES USE STANDARD SUPERDUTY SIZE TIE ROD ENDS FOR THE DRAG LINK AND TIE ROD. IT IS ABSOLUTELY CRITICAL ON REID RACING KNUCKLES THAT ALL TIE ROD ENDS ARE THE CORRECT SIZE. IMPROPER SEATING OF THE TIE ROD AND DRAG LINK ENDS INTO THE KNUCKLE'S STEERING ARM OR INSUFFICIENT TORQUE ON THE CASTLE NUTS CAN ALLOW THE TIE ROD END TO BECOME LOOSE, RESULTING IN SLOPPY STEERING OR, IF LEFT UNCORRECTED LONG ENOUGH, POSSIBLE LOSS OF STEERING.

WARRANTY

All "Off Road Products" sold by Reid Racing, Inc. are intended to be used for "off road" and "off highway" use only, and are NOT designed, manufactured or approved for use on any public road or highway. Due to the intended use of the products offered, all "Off Road Products" are sold without any warranties of fitness for purpose or use, merchantability, or any other kind, either expressed or implied, whether written or oral, by Reid Racing, Inc., or its past, present or future officers, directors, principals, agents, employees, legal representatives, trustees, parents, associates, affiliates, subsidiaries, division, partners, heirs, executors, administrators, purchasers, predecessors, or successors. The buyer of these "Off Road Products" bears and assumes the entire risk of loss or injury as to the fitness for purpose or use, merchantability, durability and performance of these "Off Road Products" and assumes the entire cost of any necessary maintenance, service or repair. Reid Racing, Inc. will not be liable for any subsequent, resulting or consequential damages, expenses, losses or injuries arising from or out of the use, misuse, or improper installation of any "Off Road Product".